

## Overview

---

Wall mount control panel for DME series



## Features

---

- Four switches, four faders and four LEDs control panel
- Wall-mountable remote control panel for GPI control
- Uses a US-type 3 gang wall box

## General Specifications

### Connector Pin Assignments

#### 8P

No.	Connection
1	S1V
2	S10
3	S2V
4	S20
5	S3V
6	S30
7	S4V
8	S40

#### 5P

No.	Connection
1	L1I
2	L2I
3	L3I
4	L4I
5	LGND

#### 9P

No.	Connection
1	F1V
2	F10
3	F2V
4	F20
5	F3V
6	F30
7	F4V
8	F40
9	FGND

### Control I/O Characteristics

Terminal		Level	Connector
GPI	IN	TTL	Euro Block Connector
	OUT	0 – 5V	Euro Block Connector
	+V	5V	Euro Block Connector

### Net Weight


0.8Kg (1.8lbs)

### Temperature Range

Conditions	Range
Operating temperature range	10 – 35°C
Storage temperature range	-20 – 60°C

## Dimensions

Unit: mm (inch)



\*All information subject to change without notice.

\*All trademarks and registered trademarks are property of their respective owners.

Created in March, 2017

YAMAHA CORPORATION  
 P.O.BOX 1, Hamamatsu Japan  
[www.yamahaproaudio.com](http://www.yamahaproaudio.com)